

CERTIFICATE

No. 30328901E/CS/28.10.16

In accordance with the Specification API 6FB
(dated December 2008) the gasket

DeltaV-Seal
6" Class 300

of the gasket manufacturer

OTECHOS AS
Fjærkleivene 52
NOR - 4902 TVEDESTRAND

was tested in respect of fire safety. The test was made under the following conditions:

Total bolt load:	842.4	kN
Burn period:	30	min
Average temperature calorimeters:	> 650	°C
Test pressure (absolute):	40	bar
Test medium:	Water	
Leak rate:	0.01	ml/(inch · min)

After the burn period the connection was air cooled to a flange temperature below 100 °C. During the cool-down the connection was still pressurized with the test pressure.

Therefore the gasket is in compliance with the tightness criteria of **1 ml/(inch · min)** of API 6FB during burn period and cool-down. The gasket manufacturer can mark the gasket as 'FIRE-SAFE' in accordance to the specification API 6FB.

This certificate is only valid in combination with the test report 3032891.

Lauffen, 28.10.2016

amtec Services GmbH



B. Eng. C. Six
Test Engineer



Dipl.-Ing. F. Herkert
Head of Laboratory



quality
certified

ISO 9001
KTA1401



Deutsche
Akkreditierungsstelle
D-PL-12008-01-00